800-955-5253 715-386-2323 866-961-5253 Parts 800-388-5253 Service 715-386-4291 FAX www.norlake.com



REFRIGERATED CHEF BASE



SPECIFICATIONS FOR: NLCB36, NLCB48, NLCB53, NLCB60, NLCB72, NLCB84, NLCB96

Complete stainless steel interior. Stainless steel exterior front, sides and Finish:

heavy-duty marine edge top (except NLCB36). NLCB36 has a flat top.

Galvanized bottom and back.

Insulation: The complete cabinet and drawers are foamed in place with polyurethane

insulation

Electrical: 115 volt, 60 Hz, 1 phase with cord and NEMA 5-15P Plug

Hardware: Heavy-duty stainless steel drawers supported on stainless steel telescoping

> drawer slides with stainless steel roller bearing wheels. Drawer slides designed to withstand maximum of 200 lbs per drawer. Full marine edge top to prevent spills from flowing over edge. Heavy-duty 4" casters. Drawers include notched locking pan adapter bars for full-size pans (pans

not included).

Refrigeration: Self-contained refrigeration system utilizes R-134a refrigerant metered by a

> capillary tube system. Automatic condensate evaporator. Interior forced air system with high humidity evaporator coils. Adjustable temperature control.

Temperature range +34°F to +38°F. Digital temperature indicator.

UL, C-UL and ETL Sanitation listed ** Approvals:





FRIGERATED CHEF BAS

STANDARD FEATURES

- Adjustable temperature control
- Automatic condensate evaporator
- Capillary tube system
- Digital temperature indicator
- Full marine edge top (except NLCB36)
- NLCB36 has a flat top
- Full size pan adapter bars (pans not included)
- 4" casters consuming 5"
- Stainless steel exterior finish
- Stainless steel interior finish
- Stainless steel drawers
- Temperature range: +34°F to +38°F
- UL, C-UL and ETL Sanitation listed **
- Warranties: 3 year parts & labor, 5 year compressor

Models	NLCB36	NLCB48	NLCB53	NLCB60	NLCB72	NLCB84	NLCB96
Crated Weight (lbs) (kg)	182 (87)	232 (105)	230 (104)	250 (113)	340 (153)	355 (160)	390 (180)
Crated Height (in) (cm)	27 (68)	27 (68)	27 (68)	27 (68)	27 (68)	27 (68)	27 (68)
Crated Width (in) (cm)	38 (97)	50 (127)	55 (138)	62 (155)	74 (185)	86 (215)	98 (245)
Crated Depth (in) (cm)	34 (85)	34 (85)	34 (85)	34 (85)	34 (85)	34 (85)	34 (85)
Interior Height (in) (cm)	16-1/2 (41)	16-1/2 (41)	16-1/2 (41)	16-1/2 (41)	16-1/2 (41)	16-1/2 (41)	16-1/2 (41)
Interior Width (in) (cm)	22-1/4 (57)	34-1/4 (87)	39-3/4 (99)	39-3/4 (99)	57-1/2 (144)	70-1/2 (176)	83-1/2 (209)
Interior Depth (in) (cm)	21-3/4 (54)	21-3/4 (54)	21-3/4 (54)	21-3/4 (54)	21-3/4 (54)	21-3/4 (54)	21-3/4 (54)
Overall Height (in) (cm)	25-1/2 (64)	25-1/2 (64)	25-1/2 (64)	25-1/2 (64)	25-1/2 (64)	25-1/2 (64)	25-1/2 (64)
Overall Width (in) (cm)	36 (92)	48 (122)	53 (133)	60 (150)	72 (180)	84 (210)	96-1/16 (240)
Overall Depth (in) (cm)	31 (78)	31 (78)	31 (78)	31 (78)	31 (78)	31 (78)	31 (78)
Gross Cubage (CuFt) (L)	5.7 (161)	8.6 (244)	9.8 (277)	9.8 (277)	14.3 (405)	17.2 (487)	21.4 (606)
Full Size Pan Capacity**	2	4	6	6	8	10	12
Number of Drawers	2	2	2	2	4	4	4
Number of Casters	4	4	4	4	6	6	6
Total Weight / Load Capacity (lbs) (kg)	1040 (468)	1040 (468)	1040 (468)	1040 (468)	1560 (702)	1560 (702)	1560 (702)
Condensing Unit Size	1/5 HP	3/8 HP	3/8 HP				
Refrigerant	R-134a	R-134a	R-134a	R-134a	R-134a	R-134a	R-134a
Electrical Characteristics	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes	Yes	Yes	Yes	Yes
NEMA Plug Configuration	5-15P	5-15P	5-15P	5-15P	5-15P	5-15P	5-15P

3.3

3.3

3.3

6.0

6.0

Specifications subject to change without notice.

3.3

3.3

Total Amp Draw

OPTIONAL FEATURES*

SPECIFICATIONS

Legs

^{*}Most options are available one week from receipt of order. Please contact us for specific questions.


^{**}C-UL is Underwriters Laboratories Safety Certification Mark which indicates that UL has tested the equipment to applicable CSA Standards

^{**}ETL Sanitation is Intertek Labs Sanitation Mark which indicates that ETL has tested the equipment to applicable NSF Standards.


^{**} Pans not included.








FRONT VIEW




TOP VIEW



NLCB48




FRONT VIEW




TOP VIEW



NLCB53





FRONT VIEW



TOP VIEW









NLCB60 FRONT VIEW TOP VIEW









NLCB72

FRONT VIEW

TOP VIEW








NLCB84

FRONT VIEW

TOP VIEW








NLCB96

FRONT VIEW

TOP VIEW









NOR-LAKE, INCORPORATED Revision Date: 05/15 © 2015 NOR-LAKE, INC. Printed in the U.S.A. Part Number: 143582

SIDE VIEW