

R8 Ultra



3
BLADES

8 Qt.



A SALES FEATURES

Vertical Cutter Mixer R8 Ultra is designed for processing both large and small quantities of meat, vegetables and smooth textured mousses, as well as for grinding and kneading food product in a minimum of time.

B TECHNICAL FEATURES

Vertical Cutter Mixer R8 Ultra. Three-Phase. Power 3 HP. 2 speeds. Pulse switch. 8 Qt. stainless-steel bowl with 2 handles. Bowl-base blade assembly with 2 detachable smooth blades included. Mini bowl 3.5 Qt. stainless steel assembly included. 20 to 150 meals.

Select all the options at the back page, **F** part.

C TECHNICAL DATA

| | |
|------------------------------|---------------------------------|
| Output power | 3 HP |
| Electrical data | 3-phase - Plug included |
| Speeds | 1800 & 3600 rpm |
| Dimensions (HxLxW) | 21 3/16" x 22 1/16" x 15 11/16" |
| Rate of recyclability | 95% |
| Net weight | 105 lbs |
| Nema # | L15-20P |
| Reference | R 8 Ultra - 208 - 240V/60/3 |

| | |
|---|------------------|
| D Number of meals per service | 20 to 150 covers |
| Working quantities per batch | 8 lbs |

E PRODUCT FEATURES/BENEFITS

MOTOR BASE

- Direct drive induction motor (no belt) for intensive use.
- Power 3 HP.
- Stainless steel motor shaft.
- Flat, easy-clean motor base.
- Magnetic safety and motor brake.
- **2 speeds : 1800 & 3600 rpm**
- Pulse function for a better cut precision.

CUTTER FUNCTION

- 8 Qt. stainless-steel bowl with 2 handles for a better grip.
- Central bowl locking system for easy assembly.
- Bowl-base blade assembly with 2 blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Transparent lid to enable user to monitor processing.
- Opening in center of lid for adding liquid or dry ingredients during processing.

INCLUDED ACCESSORIES

- Stainless steel smooth blade assembly (2 blades)
- Mini bowl : 3.5 Qt. stainless steel assembly.



Shown with mini bowl assembly

STANDARDS
ETL electrical and sanitation Listed/ cETL (Canada)



R8 Ultra

R8 Ultra

G

DRAWINGS & DIMENSIONS

208-240V/60/3 - delivered with cord and plug.

